

Description

Fastener Length: 7/8", Thread: 1/4-28, Thread Length: 7/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS27039C413 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5305-00-775-6381 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS27039C4-13 Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.461 Inches Minimum |
| Fastener Length: | 0.828 Inches Minimum And 0.876 Inches Maximum |
| Head Style: | Pan No. 2 |
| Head Diameter: | 0.473 Inches Minimum And 0.492 Inches Maximum |
| Head Height: | 0.162 Inches Minimum And 0.175 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.250 Inches |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Screw Material: | Iron Alloy 660 |
| Screw Material Document And Classification: | Ams 5735 Assn Std Single Material Response |
| Screw Surface Treatment: | Passivate |
| Thread Series Designator: | Unf |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS27039C4-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.