

**Description**

Fastener Length: 9/16", Thread: 8-32, Thread Length: 31/64",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS27039DD0808
Minimum Qty (MOQ):	25
NSN:	5305-00-925-9715
ECCN:	EAR99
National Motor Freight:	013680, Alum Screws



\* See page 2 for technical characteristics

# P/N MS27039DD0808 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.345 Inches Minimum And 0.484 Inches Maximum
Fastener Length:	0.516 Inches Minimum And 0.563 Inches Maximum
Head Style:	Pan
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	62000 Pounds Per Square Inch
Screw Material:	Aluminum Alloy 2024
Screw Surface Treatment:	Anodize
Screw Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response
Thread Series Designator:	Unc

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS27039DD0808> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.