

Description

MS27039DD0809 Machine Screw

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------|
| SKU / Model: | MS27039DD0809 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5305-00-903-7738 |
| ECCN: | EAR99 |
| National Motor Freight: | 013680, Alum Screws |

NO IMAGE
AVAILABLE

P/N MS27039DD0809 Specifications

| | |
|-------------------------------------------------------------|----------------------------------------------------------------------------------------------|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.346 Inches Minimum And 0.485 Inches Maximum |
| Fastener Length: | 0.579 Inches Minimum And 0.626 Inches Maximum |
| Head Style: | Pan |
| Head Diameter: | 0.306 Inches Minimum And 0.322 Inches Maximum |
| Head Height: | 0.105 Inches Minimum And 0.115 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.164 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 62000 Pounds Per Square Inch |
| Screw Material: | Aluminum Alloy 2024 |
| Screw Material Document And Classification: | Qq-a-225/6 Fed Spec Single Material Response Or Mil-w-7986 Mil Spec Single Material Response |
| Screw Surface Treatment: | Anodize |
| Screw Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec Single Treatment Response |
| Thread Series Designator: | Unc |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS27039DD0809> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.