

Description

Fastener Length: 1-1/2", Thread: 8-32, Thread Length: 31/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS27039DD0815
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-257-1899
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	013680, Alum Screws



* See page 2 for technical characteristics

P/N MS27039DD0815 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.969 Inches Minimum
Fastener Length:	1.500 Inches Nominal
Head Style:	Pan
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	62000 Pounds Per Square Inch
Screw Material:	Aluminum Alloy
Screw Surface Treatment:	Anodize
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS27039DD0815> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.