

Description

anodized aluminum - length: 0.719", grip: 0.250", thread: 8-32, pan head structural machine screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------|
| SKU / Model: | MS27039DD111 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5305-00-145-0959 |
| ECCN: | EAR99 |
| National Motor Freight: | 013680, Alum Screws |



* See page 2 for technical characteristics

P/N MS27039DD1-11 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.439 Inches Minimum And 0.516 Inches Maximum |
| Fastener Length: | 0.704 Inches Minimum And 0.751 Inches Maximum |
| Head Style: | Pan |
| Head Diameter: | 0.357 Inches Minimum And 0.373 Inches Maximum |
| Head Height: | 0.122 Inches Minimum And 0.133 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 62000 Pounds Per Square Inch |
| Screw Material: | Aluminum Alloy 2024 |
| Screw Material Document And Classification: | Qq-a-225/6 Fed Spec Single Material Response Or Qq-a-430 Fed Spec Single Material Response |
| Screw Surface Treatment: | Anodize |
| Screw Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec Single Treatment Response |
| Thread Series Designator: | Unf |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS27039DD1-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.