

Description

Fastener Length: 1-1/2", Thread: 10-32, Thread Length: 33/64

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS27039DD123
Minimum Qty (MOQ):	25
NSN:	5305-00-947-4286
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	013680, Alum Screws

NO IMAGE
AVAILABLE

P/N MS27039DD1-23 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.377 Inches Minimum And 0.516 Inches Maximum
Fastener Length:	1.454 Inches Minimum And 1.501 Inches Maximum
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	62000 Pounds Per Square Inch
Screw Material:	Aluminum Alloy 2024
Screw Material Document And Classification:	Qq-a-225/6 Fed Spec Single Material Response Or Mil-w-7986 Mil Spec Single Material Response
Screw Surface Treatment:	Anodize
Screw Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS27039DD1-23> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.