

Description

Fastener Length: 1-3/4", Thread: 10-32, Thread Length: 13/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------|
| SKU / Model: | MS27039DD127 |
| Minimum Qty (MOQ): | 35 EA |
| NSN: | 5305-00-855-8217 |
| Schedule B: | 7616.10.9090 |
| ECCN: | EAR99 |
| National Motor Freight: | 013680, Alum Screws |

NO IMAGE
AVAILABLE

P/N MS27039DD1-27 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.407 Inches Minimum |
| Fastener Length: | 1.704 Inches Minimum And 1.751 Inches Maximum |
| Head Style: | Pan No. 2 |
| Head Diameter: | 0.357 Inches Minimum And 0.373 Inches Maximum |
| Head Height: | 0.122 Inches Minimum And 0.133 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 62000 Pounds Per Square Inch |
| Screw Material: | Aluminum Alloy Or Aluminum Alloy 2024 |
| Screw Material Document And Classification: | Mil-w-7986 Mil Spec 1st Material Response Or Qq-a-268 T4 Fed Spec 2nd Material Response |
| Screw Surface Treatment: | Anodize |
| Screw Surface Treatment Document And Classification: | Mil-a-8625 Type 1 Or 2 Mil Spec Single Treatment Response |
| Thread Series Designator: | Unf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS27039DD1-27> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.