

**Description**

Fastener Length: 1-3/4", Thread: 10-32, Thread Length: 13/32"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS27039DD127
Minimum Qty (MOQ):	35 EA
NSN:	5305-00-855-8217
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	013680, Alum Screws

NO IMAGE  
AVAILABLE

## P/N MS27039DD1-27 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.407 Inches Minimum
<b>Fastener Length:</b>	1.704 Inches Minimum And 1.751 Inches Maximum
<b>Head Style:</b>	Pan No. 2
<b>Head Diameter:</b>	0.357 Inches Minimum And 0.373 Inches Maximum
<b>Head Height:</b>	0.122 Inches Minimum And 0.133 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	62000 Pounds Per Square Inch
<b>Screw Material:</b>	Aluminum Alloy Or Aluminum Alloy 2024
<b>Screw Material Document And Classification:</b>	Mil-w-7986 Mil Spec 1st Material Response Or Qq-a-268 T4 Fed Spec 2nd Material Response
<b>Screw Surface Treatment:</b>	Anodize
<b>Screw Surface Treatment Document And Classification:</b>	Mil-a-8625 Type 1 Or 2 Mil Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS27039DD1-27> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.