

**Description**

Fastener Length: 1-3/4", Thread: 10-32, Thread Length: 13/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS27039DD127
Minimum Qty (MOQ):	35 EA
NSN:	5305-00-855-8217
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	013680, Alum Screws



\* See page 2 for technical characteristics

# P/N MS27039DD1-27 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.407 Inches Minimum
Fastener Length:	1.704 Inches Minimum And 1.751 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	62000 Pounds Per Square Inch
Screw Material:	Aluminum Alloy Or Aluminum Alloy 2024
Screw Material Document And Classification:	Mil-w-7986 Mil Spec 1st Material Response Or Qq-a-268 T4 Fed Spec 2nd Material Response
Screw Surface Treatment:	Anodize
Screw Surface Treatment Document And Classification:	Mil-a-8625 Type 1 Or 2 Mil Spec Single Treatment Response
Thread Series Designator:	Unf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS27039DD1-27> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.