

Description

anodized aluminum, length: 1.906", grip: 1.438", thread: 8-32, pan head structural machine screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS27039DD130
Minimum Qty (MOQ):	20
NSN:	5305-01-125-9017
ECCN:	EAR99
National Motor Freight:	013680, Alum Screws



P/N MS27039DD1-30 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.438 Inches Minimum And 0.515 Inches Maximum
Fastener Length:	1.891 Inches Minimum And 1.938 Inches Maximum
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	62000 Pounds Per Square Inch
Screw Material:	Aluminum Alloy 2024
Screw Material Document And Classification:	Mil-w-7986 Mil Spec 1st Material Response Or Qq-a-225/6,t4 Mil Spec 2nd Material Response
Screw Surface Treatment Document And Classification:	Mil-a-8625,type 1 Mil Spec 1st Treatment Response Or Mil-a-8625,type 2 Mil Spec 2nd Treatment Response
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS27039DD1-30> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.