

Description

anodized aluminum, length: 1.906", grip: 1.438", thread: 8-32, pan head structural machine screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------|
| SKU / Model: | MS27039DD130 |
| Minimum Qty (MOQ): | 20 |
| NSN: | 5305-01-125-9017 |
| ECCN: | EAR99 |
| National Motor Freight: | 013680, Alum Screws |



P/N MS27039DD1-30 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.438 Inches Minimum And 0.515 Inches Maximum |
| Fastener Length: | 1.891 Inches Minimum And 1.938 Inches Maximum |
| Head Style: | Pan |
| Head Diameter: | 0.357 Inches Minimum And 0.373 Inches Maximum |
| Head Height: | 0.122 Inches Minimum And 0.133 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 62000 Pounds Per Square Inch |
| Screw Material: | Aluminum Alloy 2024 |
| Screw Material Document And Classification: | Mil-w-7986 Mil Spec 1st Material Response Or Qq-a-225/6,t4 Mil Spec 2nd Material Response |
| Screw Surface Treatment Document And Classification: | Mil-a-8625,type 1 Mil Spec 1st Treatment Response Or Mil-a-8625,type 2 Mil Spec 2nd Treatment Response |
| Thread Series Designator: | Unf |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS27039DD1-30> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.