

Description

Fastener Length: 9/16", Thread: 1/4-28, Thread Length: 17/32", MS27039 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS27039DD408
Minimum Qty (MOQ):	20
NSN:	5305-00-133-1917
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	013680, Alum Screws



P/N MS27039DD4-08 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.452 Inches Minimum And 0.531 Inches Maximum
Fastener Length:	0.516 Inches Minimum And 0.563 Inches Maximum
Head Style:	Pan
Head Diameter:	0.473 Inches Minimum And 0.492 Inches Maximum
Head Height:	0.162 Inches Minimum And 0.175 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	62000 Pounds Per Square Inch
Screw Material:	Aluminum Alloy 2024
Screw Material Document And Classification:	Qq-a-225/6 Fed Spec Single Material Response Or Qq-a-430 Fed Spec Single Material Response
Screw Surface Treatment:	Anodize
Screw Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS27039DD4-08> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.