

Description

MS27111-3 Key Washer

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS271113
Minimum Qty (MOQ):	50
NSN:	5310-00-968-3178
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



NO IMAGE
AVAILABLE

P/N MS27111-3 Specifications

Hole Diameter:	0.376 Inches Minimum And 0.386 Inches Maximum
Outside Diameter:	0.489 Inches Minimum And 0.509 Inches Maximum
External Straight Key Width:	0.130 Inches Minimum And 0.150 Inches Maximum
Internal Straight Key Width:	0.081 Inches Minimum And 0.091 Inches Maximum
Distance From Centerline To Top Of Internal Key:	0.167 Inches Nominal
Overall Distance Including Keys:	0.812 Inches Minimum And 0.832 Inches Maximum
External Key Quantity:	7
Internal Key Quantity:	1
Material Thickness:	0.027 Inches Minimum And 0.033 Inches Maximum
Material:	Steel Comp 1005 Overall Or Steel Comp 1006 Overall Or Steel Comp 1008 Overall Or Steel Comp 1010 Overall Or Steel Comp 1011 Overall Or Steel Comp 1012 Overall Or Steel Comp 1013 Overall Or Steel Comp 1015 Overall Or Steel Comp 1016 Overall Or Steel Comp 1017 Overall Or Steel Comp 1018 Overall Or Steel Comp 1019 Overall Or Steel Comp 1020 Overall Or Steel Comp 1021 Overall Or Steel Comp 1022 Overall Or Steel Comp 1026 Overall Or Steel Comp 1030 Overall Or Steel Comp 1034 Overall Or Steel Comp 1035 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,c1 3 Fed Spec Single Treatment Response Overall
Style Designator:	Key
Specification/standard Data:	80205-nas460 Professional/industrial Association Standard

How to Order

Order this key washer from our inventory online by visiting <https://military-fasteners.com/washers/key+washers/MS27111-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.