

**Description**

Thread Size: 1/4", Nut Length: 5/8"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS27130A100K
Minimum Qty (MOQ):	30 EA
NSN:	5310-01-046-3284
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS27130-A100K Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Head Style:</b>	Flat Countersunk Reverse Keyed
<b>Head Diameter:</b>	0.391 Inches Nominal
<b>Key Length:</b>	0.065 Inches Maximum
<b>Head Height:</b>	0.065 Inches Maximum
<b>Nut Style:</b>	Blind Rivet W/smooth Round Shank
<b>Nut Diameter:</b>	0.246 Inches Minimum And 0.250 Inches Maximum
<b>Nut Length:</b>	0.610 Inches Minimum And 0.640 Inches Maximum
<b>Err Default:</b>	+0.116/+0.166 Inches
<b>Shank End Type:</b>	Open
<b>End Item Identification:</b>	W/s: Aircraft, Prowler Ea-6b; Missile, Minuteman Lgm-30; Support Equipment, B-1 Aircraft; Aircraft, Viking S-3b; Aircraft, Galaxy C-5; F117a Aircraft
<b>Thread Series:</b>	Unf
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.190 Inches
<b>Head Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Aluminum Alloy 6053 Overall
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec Single Treatment Response Overall

## How to Order

Order this rivnut from our inventory online by visiting <https://military-fasteners.com/fittings/pipe+plugs/MS27130-A100K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.