

Description

Thread Size: 1/4", Nut Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-------------------|
| SKU / Model: | MS27130A100K |
| Minimum Qty (MOQ): | 30 EA |
| NSN: | 5310-01-046-3284 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013540, Alum Nuts |

NO IMAGE
AVAILABLE

P/N MS27130-A100K Specifications

| | |
|---|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Head Style: | Flat Countersunk Reverse Keyed |
| Head Diameter: | 0.391 Inches Nominal |
| Key Length: | 0.065 Inches Maximum |
| Head Height: | 0.065 Inches Maximum |
| Nut Style: | Blind Rivet W/smooth Round Shank |
| Nut Diameter: | 0.246 Inches Minimum And 0.250 Inches Maximum |
| Nut Length: | 0.610 Inches Minimum And 0.640 Inches Maximum |
| Err Default: | +0.116/+0.166 Inches |
| Shank End Type: | Open |
| End Item Identification: | W/s: Aircraft, Prowler Ea-6b; Missile, Minuteman Lgm-30; Support Equipment, B-1 Aircraft; Aircraft, Viking S-3b; Aircraft, Galaxy C-5; F117a Aircraft |
| Thread Series: | Unf |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.190 Inches |
| Head Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Aluminum Alloy 6053 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec Single Treatment Response Overall |

How to Order

Order this rivnut from our inventory online by visiting <https://military-fasteners.com/fittings/pipe+plugs/MS27130-A100K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.