

Description

Thread Size: 1/4", Nut Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS27130A100K
Minimum Qty (MOQ):	30 EA
NSN:	5310-01-046-3284
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



* See page 2 for technical characteristics

P/N MS27130-A100K Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Countersunk Reverse Keyed
Head Diameter:	0.391 Inches Nominal
Key Length:	0.065 Inches Maximum
Head Height:	0.065 Inches Maximum
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.246 Inches Minimum And 0.250 Inches Maximum
Nut Length:	0.610 Inches Minimum And 0.640 Inches Maximum
Err Default:	+0.116/+0.166 Inches
Shank End Type:	Open
End Item Identification:	W/s: Aircraft, Prowler Ea-6b; Missile, Minuteman Lgm-30; Support Equipment, B-1 Aircraft; Aircraft, Viking S-3b; Aircraft, Galaxy C-5; F117a Aircraft
Thread Series:	Unf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Head Countersink Angle:	100.0 Degrees Nominal
Material:	Aluminum Alloy 6053 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall

How to Order

Order this rivnut from our inventory online by visiting <https://military-fasteners.com/fittings/pipe+plugs/MS27130-A100K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.