

**Description**

grip range: 0.075" - 0.120", thread: 8-32, rivnut, aluminum, flat head, MS27130 series nut

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS27130A14
Minimum Qty (MOQ):	50
NSN:	5310-00-207-5275
Schedule B:	7616.10.1000
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts

NO IMAGE  
AVAILABLE

## P/N MS27130-A14 Specifications

<b>Thread Class:</b>	2b
<b>Thread Direction:</b>	Right-hand
<b>Head Style:</b>	Flat
<b>Head Diameter:</b>	0.357 Inches Nominal
<b>Head Height:</b>	0.032 Inches Nominal
<b>Nut Style:</b>	Blind Rivet W/smooth Round Shank
<b>Nut Diameter:</b>	0.221 Inches Nominal
<b>Nut Length:</b>	0.500 Inches Nominal
<b>Err Default:</b>	+0.075/+0.120 Inches
<b>Unable To Decode:</b>	+0.075 To 0.120 Inches
<b>Shank End Type:</b>	Open
<b>Thread Series:</b>	Unc
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.164 Inches
<b>Material:</b>	Aluminum Alloy 6063 Overall
<b>Material Document And Classification:</b>	Qq-a-430,t4 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall

## How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/MS27130-A14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.