

Description

Plain Blind Rivet Nut part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS27130A15K
Minimum Qty (MOQ):	25
NSN:	5310-00-188-7972
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS27130-A15K Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Keyed
Head Diameter:	0.342 Inches Minimum And 0.372 Inches Maximum
Key Length:	0.055 Inches Nominal
Head Height:	0.032 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.217 Inches Minimum And 0.221 Inches Maximum
Nut Length:	0.485 Inches Minimum And 0.515 Inches Maximum
Err Default:	+0.120/+0.160 Inches
Unable To Decode:	+0.120 To 0.160 Inches
Shank End Type:	Open
Thread Series:	Unc
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Material:	Aluminum Alloy 5005 Overall
Material Document And Classification:	H14 Assn Std Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1329 Professional/industrial Association Standard

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/MS27130-A15K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.