

Description

Thread Size: 3/8", Nut Length: 7/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS27130A61
Minimum Qty (MOQ):	5 EA
NSN:	5310-01-046-5383
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS27130-A61 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat
Head Diameter:	0.766 Inches Minimum And 0.796 Inches Maximum
Head Height:	0.088 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.486 Inches Minimum And 0.490 Inches Maximum
Nut Length:	0.829 Inches Minimum And 0.859 Inches Maximum
Err Default:	+0.030/+0.115 Inches
Shank End Type:	Open
Thread Series:	Unf
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.375 Inches
Material:	Aluminum Alloy 6053 Overall
Material Document And Classification:	Qq-a-430 T4 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Ty 2 Mil Spec Single Treatment Response Overall

How to Order

Order this rivnut from our inventory online by visiting <https://military-fasteners.com/fittings/pipe+plugs/MS27130-A61> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.