

**Description**

Thread Size: 3/8", Nut Length: 1"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS27130CR56K
Minimum Qty (MOQ):	5 EA
NSN:	5310-00-425-0754
Schedule B:	7318.16.0085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS27130-CR56K Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Head Style:</b>	Flat Keyed
<b>Head Diameter:</b>	0.766 Inches Minimum And 0.796 Inches Maximum
<b>Key Length:</b>	0.128 Inches Maximum
<b>Head Height:</b>	0.088 Inches Nominal
<b>Locking Feature:</b>	Prevailing Torque All Metal Design
<b>Nut Style:</b>	Blind Rivet W/smooth Round Shank
<b>Nut Diameter:</b>	0.486 Inches Minimum And 0.490 Inches Maximum
<b>Nut Length:</b>	0.923 Inches Minimum And 0.953 Inches Maximum
<b>Nut Grip Range:</b>	+0.115/+0.200 Inches
<b>Unable To Decode:</b>	+0.115 To 0.200 Inches
<b>Shank End Type:</b>	Open
<b>Thread Series:</b>	Unc
<b>Thread Quantity Per Inch:</b>	16
<b>Nominal Thread Size:</b>	0.375 Inches
<b>Material:</b>	Steel Comp 430 Overall
<b>Material Document And Classification:</b>	Aisi Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall

## How to Order

Order this rivnut from our inventory online by visiting <https://military-fasteners.com/fittings/pipe+plugs/MS27130-CR56K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.