

Description

Thread Size: 3/8", Nut Length: 1"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS27130CR56K
Minimum Qty (MOQ):	5 EA
NSN:	5310-00-425-0754
Schedule B:	7318.16.0085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS27130-CR56K Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Keyed
Head Diameter:	0.766 Inches Minimum And 0.796 Inches Maximum
Key Length:	0.128 Inches Maximum
Head Height:	0.088 Inches Nominal
Locking Feature:	Prevailing Torque All Metal Design
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.486 Inches Minimum And 0.490 Inches Maximum
Nut Length:	0.923 Inches Minimum And 0.953 Inches Maximum
Nut Grip Range:	+0.115/+0.200 Inches
Unable To Decode:	+0.115 To 0.200 Inches
Shank End Type:	Open
Thread Series:	Unc
Thread Quantity Per Inch:	16
Nominal Thread Size:	0.375 Inches
Material:	Steel Comp 430 Overall
Material Document And Classification:	Aisi Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

How to Order

Order this rivnut from our inventory online by visiting <https://military-fasteners.com/fittings/pipe+plugs/MS27130-CR56K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.