

Description

Thread Size: 5/32", Nut Length: 1/2", rivnut, MS27130 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS27130S14K
Minimum Qty (MOQ):	25
NSN:	5310-01-036-0908
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS27130-S14K Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Keyed
Head Diameter:	0.342 Inches Minimum And 0.372 Inches Maximum
Key Length:	0.055 Inches Nominal
Head Height:	0.032 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.217 Inches Minimum And 0.221 Inches Maximum
Nut Length:	0.485 Inches Minimum And 0.515 Inches Maximum
Err Default:	+0.075/+0.089 Inches
Shank End Type:	Open
Thread Series:	Unc
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Material:	Steel Comp 1108 Overall Or Steel Comp 1110 Overall
Material Document And Classification:	Aisi Assn Std 1st Material Response Overall Or Sae Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/MS27130-S14K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.