

**Description**

Thread Size: 5/32", Nut Length: 1/2", rivnut, MS27130 series nut

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS27130S14K
Minimum Qty (MOQ):	25
NSN:	5310-01-036-0908
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N MS27130-S14K Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Head Style:</b>	Flat Keyed
<b>Head Diameter:</b>	0.342 Inches Minimum And 0.372 Inches Maximum
<b>Key Length:</b>	0.055 Inches Nominal
<b>Head Height:</b>	0.032 Inches Nominal
<b>Nut Style:</b>	Blind Rivet W/smooth Round Shank
<b>Nut Diameter:</b>	0.217 Inches Minimum And 0.221 Inches Maximum
<b>Nut Length:</b>	0.485 Inches Minimum And 0.515 Inches Maximum
<b>Err Default:</b>	+0.075/+0.089 Inches
<b>Shank End Type:</b>	Open
<b>Thread Series:</b>	Unc
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.164 Inches
<b>Material:</b>	Steel Comp 1108 Overall Or Steel Comp 1110 Overall
<b>Material Document And Classification:</b>	Aisi Assn Std 1st Material Response Overall Or Sae Assn Std 2nd Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

## How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/MS27130-S14K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.