

Description

Thread Size: 5/32", Nut Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-------------------|
| SKU / Model: | MS27130S15K |
| Minimum Qty (MOQ): | 30 EA |
| NSN: | 5310-01-036-4687 |
| Schedule B: | 7318.16.0085 |
| ECCN: | EAR99 |
| National Motor Freight: | 013540, Alum Nuts |

NO IMAGE
AVAILABLE

P/N MS27130-S15K Specifications

| | |
|---|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Head Style: | Flat Keyed |
| Head Diameter: | 0.342 Inches Minimum And 0.372 Inches Maximum |
| Key Length: | 0.055 Inches Nominal |
| Head Height: | 0.032 Inches Nominal |
| Nut Style: | Blind Rivet W/smooth Round Shank |
| Nut Diameter: | 0.217 Inches Minimum And 0.221 Inches Maximum |
| Nut Length: | 0.485 Inches Minimum And 0.515 Inches Maximum |
| Err Default: | +0.120/+0.160 Inches |
| Shank End Type: | Open |
| Thread Series: | Unc |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.164 Inches |
| Material: | Steel Comp 1108 Overall Or Steel Comp 1110 Overall |
| Material Document And Classification: | Aisi Assn Std 1st Material Response Overall Or Sae Assn Std 2nd Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |

How to Order

Order this rivnut from our inventory online by visiting <https://military-fasteners.com/fittings/pipe+plugs/MS27130-S15K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.