

Description

Thread Size: 1/4", Nut Length: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS27130S43
Minimum Qty (MOQ):	30 EA
NSN:	5310-00-080-2411
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS27130-S43 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat
Head Diameter:	0.650 Inches Minimum And 0.680 Inches Maximum
Head Height:	0.062 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.413 Inches Maximum
Nut Length:	0.735 Inches Minimum And 0.765 Inches Maximum
Err Default:	+0.050/+0.125 Inches
Unable To Decode:	+0.050 To 0.125 Inches
Shank End Type:	Open
Thread Series:	Unc
Thread Quantity Per Inch:	18
Nominal Thread Size:	0.312 Inches
Material:	Steel Comp 1108 Overall Or Steel Comp 1120 Overall
Material Document And Classification:	Sae Assn Std 1st Material Response Overall Or Aisi Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 1,c1 3 Fed Spec Single Treatment Response Overall

How to Order

Order this rivnut from our inventory online by visiting <https://military-fasteners.com/fittings/pipe+plugs/MS27130-S43> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.