

P/N MS27130-S99

Military-Fasteners.com

### Description

MS27130-S99 Plain Blind Rivet Nut

\* Manufacturer certifications are shipped with your order  $\underline{\mathsf{FREE}}$  of charge

## Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

#### MS27130S99 AES10-116CSI NAS1330S3-116

SKU / Model:	MS27130S99
Minimum Qty (MOQ):	50
NSN:	5310-00-999-4016
ECCN:	EAR99
National Motor Freight:	077140, Fruits Dried / Evaporated Noi



# P/N MS27130-S99 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Countersunk
Head Diameter:	0.391 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.246 Inches Minimum And 0.250 Inches Maximum
Nut Length:	0.563 Inches Minimum And 0.593 Inches Maximum
Err Default:	+0.065/+0.116 Inches
Shank End Type:	Open
Thread Series:	Unf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Head Countersink Angle:	99.00 Degrees Minimum And 101.00 Degrees Maximum
Material:	Steel Comp 1108 Overall
Material Document And Classification:	Qq-s-633-canc Fed Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1330 Professional/industrial Association Standard

# How to Order

Order this plain blind rivet nut from our inventory online by visiting <u>https://military-fasteners.com/nuts/plain+blind+rivet+nuts/MS27130-S99</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.