

**Description**

aluminum - flat head - grip range: 0.010" - 0.060", thread: 4-40, rivnut blind rivet nut

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS27130A1
Minimum Qty (MOQ):	25
NSN:	5310-00-639-7610
National Motor Freight:	013540, Alum Nuts

NO IMAGE  
AVAILABLE

## P/N MS27130A1 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Head Style:</b>	Flat
<b>Head Diameter:</b>	0.255 Inches Minimum And 0.285 Inches Maximum
<b>Head Height:</b>	0.025 Inches Nominal
<b>Nut Style:</b>	Blind Rivet W/smooth Round Shank
<b>Nut Diameter:</b>	0.151 Inches Minimum And 0.155 Inches Maximum
<b>Nut Length:</b>	0.370 Inches Nominal
<b>Err Default:</b>	+0.010/+0.060 Inches
<b>Unable To Decode:</b>	+0.010 To 0.060 Inches
<b>Shank End Type:</b>	Open
<b>Thread Series:</b>	Unc
<b>Thread Quantity Per Inch:</b>	40
<b>Nominal Thread Size:</b>	0.112 Inches
<b>Material:</b>	Aluminum Alloy 6053 Overall
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625,ty 2 Mil Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1329 Professional/industrial Association Standard

## How to Order

Order this plain blind rivet nuts from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/MS27130A1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.