

Description

aluminum, flat head, keyed grip range: 0.010" - 0.075", thread: 8-32, rivnut, blind rivet nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[MS27130-A13K](#) [NAS1329A08K75](#)

SKU / Model:	MS27130A13K
Minimum Qty (MOQ):	50
NSN:	5310-01-099-9528
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts

NO IMAGE
AVAILABLE

P/N MS27130A13K Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Keyed
Head Diameter:	0.342 Inches Minimum And 0.372 Inches Maximum
Key Length:	0.023 Inches Maximum
Head Height:	0.032 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.217 Inches Minimum And 0.221 Inches Maximum
Nut Length:	0.423 Inches Minimum And 0.453 Inches Maximum
Err Default:	+0.010/+0.075 Inches
Shank End Type:	Open
Thread Series:	Unc
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Material:	Aluminum Alloy 6053 Overall
Material Document And Classification:	Qq-a-430,except Temper T4 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,type 2 Mil Spec Single Treatment Response Overall

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/MS27130A13K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.