

Description

grip range: 0.075" - 0.120", thread: 8-32, rivnut, aluminum, flat head, MS27130 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS27130A14
Minimum Qty (MOQ):	50
NSN:	5310-00-207-5275
National Motor Freight:	013540, Alum Nuts



P/N MS27130A14 Specifications

Thread Class:	2b
Thread Direction:	Right-hand
Head Style:	Flat
Head Diameter:	0.357 Inches Nominal
Head Height:	0.032 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.221 Inches Nominal
Nut Length:	0.500 Inches Nominal
Err Default:	+0.075/+0.120 Inches
Unable To Decode:	+0.075 To 0.120 Inches
Shank End Type:	Open
Thread Series:	Unc
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Material:	Aluminum Alloy 6063 Overall
Material Document And Classification:	Qq-a-430,t4 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/MS27130A14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.