

Description

grip range: 0.075" - 0.120", thread: 8-32, rivnut, aluminum, flat head, MS27130 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------|
| SKU / Model: | MS27130A14 |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5310-00-207-5275 |
| National Motor Freight: | 013540, Alum Nuts |



P/N MS27130A14 Specifications

| | |
|----------------------------------------------|-------------------------------------------------------|
| Thread Class: | 2b |
| Thread Direction: | Right-hand |
| Head Style: | Flat |
| Head Diameter: | 0.357 Inches Nominal |
| Head Height: | 0.032 Inches Nominal |
| Nut Style: | Blind Rivet W/smooth Round Shank |
| Nut Diameter: | 0.221 Inches Nominal |
| Nut Length: | 0.500 Inches Nominal |
| Err Default: | +0.075/+0.120 Inches |
| Unable To Decode: | +0.075 To 0.120 Inches |
| Shank End Type: | Open |
| Thread Series: | Unc |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.164 Inches |
| Material: | Aluminum Alloy 6063 Overall |
| Material Document And Classification: | Qq-a-430,t4 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/MS27130A14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.