



Military-Fasteners.com

P/N MS27130A20

Description

aluminum - flat head - grip range: 0.080" - 0.130", thread: 10-24, rivnut blind rivet nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS27130A20
Minimum Qty (MOQ):	10
NSN:	5310-01-515-4188
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS27130A20 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Keyed
Head Diameter:	0.391 Inches Minimum And 0.421 Inches Maximum
Key Length:	0.023 Inches Nominal
Head Height:	0.038 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.302 Inches Nominal
Nut Length:	0.579 Inches Minimum And 0.609 Inches Maximum
Err Default:	+0.080/+0.130 Inches
Thread Series:	Unc
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.190 Inches
Part Name Assigned By Controlling Agency:	Nut, Plain, Blind Rivet, Flat Head
Special Features:	Shank Diamer 0.250 In Min, 0.254 In Max
Material:	Steel Overall

How to Order

Order this plain blind rivet nuts from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/MS27130A20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.