

Description

aluminum - flat head - keyed grip range: 0.010" - 0.080", thread: 10-32, rivnut blind rivet nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------|
| SKU / Model: | MS27130A25K |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5310-00-225-4680 |
| National Motor Freight: | 013540, Alum Nuts |

NO IMAGE
AVAILABLE

P/N MS27130A25K Specifications

| | |
|---|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Head Style: | Flat Keyed |
| Head Diameter: | 0.391 Inches Minimum And 0.421 Inches Maximum |
| Key Length: | 0.061 Inches Nominal |
| Head Height: | 0.038 Inches Nominal |
| Nut Style: | Blind Rivet W/smooth Round Shank |
| Nut Diameter: | 0.246 Inches Minimum And 0.250 Inches Maximum |
| Nut Length: | 0.516 Inches Minimum And 0.546 Inches Maximum |
| Err Default: | +0.010/+0.080 Inches |
| Unable To Decode: | +0.010 To 0.080 Inches |
| Shank End Type: | Open |
| Thread Series: | Unf |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.190 Inches |
| Material: | Aluminum Alloy 6053 Overall |
| Material Document And Classification: | Qq-a-430,temp T4 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625,ty 2 Mil Spec Single Treatment Response Overall |

How to Order

Order this plain blind rivet nuts from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/MS27130A25K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.