

Description

Aluminum, flat head, grip range: 0.080" - 0.130", thread: 10-32, plain blind rivet nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[NAS1329A3-130](#) [MS27130-A26](#)

SKU / Model:	MS27130A26
Minimum Qty (MOQ):	50
NSN:	5310-00-141-3062
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



* See page 2 for technical characteristics

P/N MS27130A26 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat
Head Diameter:	0.391 Inches Minimum And 0.421 Inches Maximum
Head Height:	0.038 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.246 Inches Minimum And 0.250 Inches Maximum
Nut Length:	0.579 Inches Minimum And 0.609 Inches Maximum
Err Default:	+0.080/+0.130 Inches
Unable To Decode:	+0.080 To 0.130 Inches
Shank End Type:	Open
lii End Item Identification:	Mrap - Cougar
Thread Series:	Unf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Material:	Aluminum Alloy 6053 Overall
Material Document And Classification:	Qq-a-430,t4 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty 2 Mil Spec Single Treatment Response Overall

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/MS27130A26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.