

Description

Thread Size: 1/4", Nut Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS27130A37
Minimum Qty (MOQ):	15 EA
NSN:	5310-00-126-5168
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	013540, Alum Nuts

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS27130A37 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat
Head Diameter:	0.475 Inches Nominal
Head Height:	0.058 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.328 Inches Minimum And 0.332 Inches Maximum
Nut Length:	0.625 Inches Nominal
Err Default:	+0.020/+0.080 Inches
Unable To Decode:	+0.020 To 0.080 Inches
Shank End Type:	Open
Thread Series:	Unf
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Material:	Aluminum Alloy 6053 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty 2 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1329 Professional/Industrial Association Standard

How to Order

Order this rivnut from our inventory online by visiting <https://military-fasteners.com/fittings/pipe+plugs/MS27130A37> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.