

## Description

aluminum - countersunk head - keyed grip range: 0.065" - 0.106", thread: 6-32, rivnut blind rivet nut

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS27130A87K
Minimum Qty (MOQ):	25
NSN:	5310-01-215-9132
National Motor Freight:	013540, Alum Nuts



## P/N MS27130A87K Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Head Style:</b>	Flat Countersunk Reverse Keyed
<b>Head Diameter:</b>	0.315 Inches Minimum And 0.340 Inches Maximum
<b>Key Length:</b>	0.032 Inches Maximum
<b>Head Height:</b>	0.032 Inches Nominal
<b>Nut Style:</b>	Blind Rivet W/smooth Round Shank
<b>Nut Diameter:</b>	0.185 Inches Minimum And 0.189 Inches Maximum
<b>Nut Length:</b>	0.422 Inches Minimum And 0.452 Inches Maximum
<b>Err Default:</b>	+0.065/+0.106 Inches
<b>Shank End Type:</b>	Open
<b>Thread Series:</b>	Unc
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.138 Inches
<b>Head Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Aluminum Alloy 6053 Overall
<b>Material Document And Classification:</b>	Qq-a-430 T4 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Ty 2 Mil Spec Single Treatment Response Overall

## How to Order

Order this plain blind rivet nuts from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/MS27130A87K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.