

## Description

grip range: 0.065" - 0.106", thread: 8-32, aluminum, countersunk head

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

### Alternate Part Numbers

[A8-106](#) [AEIA8-106](#) [NAS1330A08-106](#) [MS27130-A93](#)

SKU / Model:	MS27130A93
Minimum Qty (MOQ):	50
NSN:	5310-01-164-4694
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



## P/N MS27130A93 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.355 Inches Nominal
<b>Nut Style:</b>	Blind Rivet W/smooth Round Shank
<b>Nut Diameter:</b>	0.217 Inches Minimum And 0.221 Inches Maximum
<b>Nut Length:</b>	0.485 Inches Minimum And 0.515 Inches Maximum
<b>Err Default:</b>	+0.065/+0.106 Inches
<b>Shank End Type:</b>	Open
<b>Thread Series:</b>	Unc
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.164 Inches
<b>Head Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Aluminum Alloy 6053 Overall
<b>Material Document And Classification:</b>	Qq-a-430,t4 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625,type 2 Mil Spec Single Treatment Response Overall
<b>Supplementary Features:</b>	Supersedes Nas1330a08-106 Replaces Nsn5310-00-079-2368
<b>Specification/standard Data:</b>	96906-ms27130 Government Standard

## How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/MS27130A93> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.