

**Description**

aluminum - flat head - keyed grip range: 0.120" - 0.106", thread: 6-32, rivnut blind rivet nut

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                   |
|-------------------------|-------------------|
| SKU / Model:            | MS27130A9K        |
| Minimum Qty (MOQ):      | 25                |
| NSN:                    | 5310-00-787-3773  |
| National Motor Freight: | 013540, Alum Nuts |

NO IMAGE  
AVAILABLE

## P/N MS27130A9K Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3b   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Head Style:</b>                                    | Flat Keyed   |
| <b>Head Diameter:</b>                                 | 0.310 Inches Minimum And 0.340 Inches Maximum              |
| <b>Key Length:</b>                                    | 0.055 Inches Nominal                                       |
| <b>Head Height:</b>                                   | 0.032 Inches Nominal                                       |
| <b>Nut Style:</b>                                     | Blind Rivet W/smooth Round Shank                           |
| <b>Nut Diameter:</b>                                  | 0.185 Inches Minimum And 0.189 Inches Maximum              |
| <b>Nut Length:</b>                                    | 0.485 Inches Minimum And 0.515 Inches Maximum              |
| <b>Err Default:</b>                                   | +0.120/+0.160 Inches                                       |
| <b>Unable To Decode:</b>                              | +0.120 To 0.160 Inches                                     |
| <b>Shank End Type:</b>                                | Open   |
| <b>Thread Series:</b>                                 | Unc  |
| <b>Thread Quantity Per Inch:</b>                      | 32   |
| <b>Nominal Thread Size:</b>                           | 0.138 Inches   |
| <b>Material:</b>                                      | Aluminum Alloy 6061 Overall                                |
| <b>Material Document And Classification:</b>          | Qq-a-430,t4 Fed Spec Single Material Response Overall      |
| <b>Surface Treatment:</b>                             | Anodize Overall  |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625,ty 2 Mil Spec Single Treatment Response Overall |

## How to Order

Order this plain blind rivet nuts from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/MS27130A9K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.