

Description

Thread Size: 1/4", Nut Length: 1/2", Rivnut, MS27130 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS27130CR25 |
| Minimum Qty (MOQ): | 15 |
| NSN: | 5310-00-440-9231 |
| Schedule B: | 7318.16.0085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS27130CR25 Specifications

| | |
|---|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Head Style: | Flat |
| Head Diameter: | 0.391 Inches Minimum And 0.421 Inches Maximum |
| Head Height: | 0.038 Inches Nominal |
| Nut Style: | Blind Rivet W/smooth Round Shank |
| Nut Diameter: | 0.246 Inches Minimum And 0.250 Inches Maximum |
| Nut Length: | 0.516 Inches Minimum And 0.546 Inches Maximum |
| Err Default: | +0.010/+0.080 Inches |
| Unable To Decode: | +0.010 To 0.080 Inches |
| Shank End Type: | Open |
| Thread Series: | Unf |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.190 Inches |
| Material: | Steel Comp 430 Overall |
| Material Document And Classification: | Qq-w-423,form 1 Fed Spec Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Type 3 Fed Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas1329 Professional/Industrial Association Standard |

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/MS27130CR25> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.