

## P/N MS27130S100

## **Description**

grip range: 0.116" - 0.166", thread: 10-32, steel, countersunk head

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

#### **Alternate Part Numbers**

AEIS10-166CSI MS27130-S100 NAS1330S3-166

SKU / Model: MS27130S100

Minimum Qty (MOQ): 25

NSN: 5310-01-020-5942

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS27130S100 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Countersunk
Head Diameter:	0.391 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.246 Inches Minimum And 0.250 Inches Maximum
Nut Length:	0.610 Inches Minimum And 0.640 Inches Maximum
Err Default:	+0.116/+0.166 Inches
Shank End Type:	Open
Thread Series:	Unf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Head Countersink Angle:	100.00 Degrees Nominal
Material:	Steel Comp 1108 Overall Or Steel Comp 1110 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

## **How to Order**

Order this plain blind rivet nut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/plain+blind+rivet+nuts/MS27130S100">https://military-fasteners.com/nuts/plain+blind+rivet+nuts/MS27130S100</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/plain+blind+rivet+nuts/MS27130S100">https://military-fasteners.com/nuts/plain+blind+rivet+nuts/MS27130S100</a> and selecting the