

## P/N MS27130S102K

## **Description**

Thread Size: 1/4", Nut Length: 3/4"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS27130S102K

Minimum Qty (MOQ): 10

NSN: 5310-00-999-4194

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS27130S102K Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Countersunk Reverse Keyed
Head Diameter:	0.391 Inches Nominal
Key Length:	0.065 Inches Maximum
Head Height:	0.065 Inches Maximum
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.246 Inches Minimum And 0.250 Inches Maximum
Nut Length:	0.719 Inches Minimum And 0.749 Inches Maximum
Err Default:	+0.216/+0.266 Inches
Shank End Type:	Open
Thread Series:	Unf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Head Countersink Angle:	99.00 Degrees Minimum And 101.00 Degrees Maximum
Material:	Steel Comp 1108 Overall
Material Document And Classification:	Qq-s-633-canc Fed Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1330 Professional/industrial Association Standard

### **How to Order**

Order this plain blind rivet nuts from our inventory online by visiting <a href="https://military-fasteners.com/nuts/plain+blind+rivet+nuts/MS27130S102K">https://military-fasteners.com/nuts/plain+blind+rivet+nuts/MS27130S102K</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.