

**Description**

steel - flat head - grip range: 0.010" - 0.080", thread: 10-32, rivnut blind rivet nut

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS27130S25
Minimum Qty (MOQ):	10
NSN:	5310-00-990-1361
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS27130S25 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Head Style:</b>	Flat
<b>Head Diameter:</b>	0.391 Inches Minimum And 0.421 Inches Maximum
<b>Head Height:</b>	0.038 Inches Nominal
<b>Nut Style:</b>	Blind Rivet W/smooth Round Shank
<b>Nut Diameter:</b>	0.246 Inches Minimum And 0.250 Inches Maximum
<b>Nut Length:</b>	0.516 Inches Minimum And 0.546 Inches Maximum
<b>Err Default:</b>	+0.010/+0.080 Inches
<b>Shank End Type:</b>	Open
<b>Thread Series:</b>	Unf
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.190 Inches
<b>Material:</b>	Steel Comp 1108 Overall Or Steel Comp 1110 Overall
<b>Material Document And Classification:</b>	Fed Std 66 Fed Std All Material Responses Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

## How to Order

Order this plain blind rivet nuts from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/MS27130S25> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.