

**Description**

grip range: 0.08" - 0.14", thread: 1/4-20, steel, flat head, rivnut

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS27130S32
Minimum Qty (MOQ):	25
NSN:	5310-00-006-8291
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



## P/N MS27130S32 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Head Style:</b>	Flat
<b>Head Diameter:</b>	0.460 Inches Minimum And 0.490 Inches Maximum
<b>Head Height:</b>	0.058 Inches Nominal
<b>Nut Style:</b>	Blind Rivet W/smooth Round Shank
<b>Nut Diameter:</b>	0.328 Inches Minimum And 0.332 Inches Maximum
<b>Nut Length:</b>	0.672 Inches Minimum And 0.702 Inches Maximum
<b>Err Default:</b>	+0.080/+0.140 Inches
<b>Unable To Decode:</b>	+0.080 To 0.140 Inches
<b>Shank End Type:</b>	Open
<b>Thread Series:</b>	Unc
<b>Thread Quantity Per Inch:</b>	20
<b>Nominal Thread Size:</b>	0.250 Inches
<b>Material:</b>	Steel Comp 1108 Overall Or Steel Comp 1110 Overall
<b>Material Document And Classification:</b>	66 Fed Std All Material Responses Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

## How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/MS27130S32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.