

Description

grip range: 0.08" - 0.14", thread: 1/4-20, steel, flat head, rivnut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------|
| SKU / Model: | MS27130S32 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5310-00-006-8291 |
| ECCN: | EAR99 |
| National Motor Freight: | 013540, Alum Nuts |



P/N MS27130S32 Specifications

| | |
|---|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Head Style: | Flat |
| Head Diameter: | 0.460 Inches Minimum And 0.490 Inches Maximum |
| Head Height: | 0.058 Inches Nominal |
| Nut Style: | Blind Rivet W/smooth Round Shank |
| Nut Diameter: | 0.328 Inches Minimum And 0.332 Inches Maximum |
| Nut Length: | 0.672 Inches Minimum And 0.702 Inches Maximum |
| Err Default: | +0.080/+0.140 Inches |
| Unable To Decode: | +0.080 To 0.140 Inches |
| Shank End Type: | Open |
| Thread Series: | Unc |
| Thread Quantity Per Inch: | 20 |
| Nominal Thread Size: | 0.250 Inches |
| Material: | Steel Comp 1108 Overall Or Steel Comp 1110 Overall |
| Material Document And Classification: | 66 Fed Std All Material Responses Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/MS27130S32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.