

Description

grip range: 0.08" - 0.14", thread: 1/4-20, steel, flat head, rivnut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS27130S32
Minimum Qty (MOQ):	25
NSN:	5310-00-006-8291
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



P/N MS27130S32 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat
Head Diameter:	0.460 Inches Minimum And 0.490 Inches Maximum
Head Height:	0.058 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.328 Inches Minimum And 0.332 Inches Maximum
Nut Length:	0.672 Inches Minimum And 0.702 Inches Maximum
Err Default:	+0.080/+0.140 Inches
Unable To Decode:	+0.080 To 0.140 Inches
Shank End Type:	Open
Thread Series:	Unc
Thread Quantity Per Inch:	20
Nominal Thread Size:	0.250 Inches
Material:	Steel Comp 1108 Overall Or Steel Comp 1110 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/MS27130S32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.