

P/N MS27151-16

Description

thread: 5/16-24

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS2715116

Minimum Qty (MOQ): 50

NSN: 5310-00-951-3174

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS27151-16 Specifications

Mating Member Diameter Accommodated:	0.312 Inches Nominal
Nut Style:	Stamped
Nut Height:	0.119 Inches Minimum And 0.139 Inches Maximum
Gripping Notch Quantity:	9
Width Across Flats:	0.489 Inches Minimum And 0.500 Inches Maximum
Material:	Steel Comp 1050 Overall Or Steel Comp 1551 Overall Or Steel Comp 1552 Overall Or Steel Comp 1053 Overall Or Steel Comp 1055 Overall Or Steel Comp 1059 Overall Or Steel Comp 1060 Overall Or Steel Comp 1561 Overall Or Steel Comp 1566 Overall Or Steel Comp 1566 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

How to Order

Order this stamped nut from our inventory online by visiting https://military-fasteners.com/nuts/stamped+nuts/MS27151-16 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/stamped+nuts/MS27151-16 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/stamped+nuts/MS27151-16 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/stamped+nuts/MS27151-16 and selecting the quantity you want https://military-fasteners.com/nuts/stamped-nuts/ms27151-16 and selecting the quantity you want https://military-fasteners.com/nuts/stamped-nuts/ms27151-16 and selecting the quantity you want https://military-fasteners.com/nuts/stamped-nuts/ms27151-16 and selecting the property of the prope