

P/N MS27183-27

Description

Hole Diameter: 1-5/64", Diameter: 1-63/64", Thickness: 5/32", MS27183 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS2718327

Minimum Qty (MOQ): 25

NSN: 5310-00-809-8541

Schedule B: 7318.22.0000

ECCN: EAR99

National Motor Freight: 194160, Washer Or Gaskets, Iron Or Steel,









^{*} See page 2 for technical characteristics

P/N MS27183-27 Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	1.055 Inches Minimum And 1.092 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Thickness:	0.108 Inches Minimum And 0.160 Inches Maximum
Overall Diameter:	1.993 Inches Minimum And 2.030 Inches Maximum
Material:	Steel Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Nondefinitive Spec/std Data:	A Type And 1 Grade And A Class
Departure From Cited Designator:	As Modified By The Finish

How to Order

Order this flat washer from our inventory online by visiting https://military-fasteners.com/washers/flat+washers/MS27183-27 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/washers/flat+washers/MS27183-27 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/washers/flat+washers/MS27183-27 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/washers/flat+washers/MS27183-27 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/washers/ms27183-27 and selecting the quantity you want the property of the propert