

Description

Hole Diameter: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2719612
Minimum Qty (MOQ):	1
NSN:	5330-00-944-5940
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



* See page 2 for technical characteristics

P/N MS27196-12 Specifications

Cross-sectional Shape Style:	Metal And Synthetic Rubber
Hole Diameter:	0.200 Inches Minimum And 0.215 Inches Maximum
Temp Rating:	-20.0 Deg Fahrenheit And 400.0 Deg Fahrenheit
Bolt Circle Diameter:	1.630 Inches Minimum And 1.640 Inches Maximum
Overall Width:	2.073 Inches Nominal
Aperture Diameter:	0.664 Inches Minimum And 0.674 Inches Maximum
Outside Corner Radius:	0.203 Inches Minimum And 0.234 Inches Maximum
Outside Corner Inverted Radius:	0.203 Inches Minimum And 0.234 Inches Maximum
Side Radius From Gasket Center:	0.620 Inches Minimum And 0.630 Inches Maximum
Cross-sectional Thickness:	0.132 Inches Nominal
Gage Ring Thickness:	0.084 Inches Minimum And 0.100 Inches Maximum
Bolt Hole Quantity:	4
Elongation Percentage:	125 Maximum
Hardness Rating:	75.0 Shore Durometer A Nominal Overall
Material:	Steel Comp 302 Overall And Rubber Fluorocarbon Class Fpm Overall
Material Document And Classification:	Mil-s-5059 Mil Spec 1st Material Response Overall And Mil-r-83248 Ty 2,cl 1 Mil Spec 2nd Material Response Overall
Style Designator:	Non-circular

How to Order

Order this gasket from our inventory online by visiting <https://military-fasteners.com/gaskets/gaskets/MS27196-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.