

Description

stud thread: 6-32, last number indicates number of studs, MS27212 series terminal

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2721212
Minimum Qty (MOQ):	2
NSN:	5940-00-950-1610
Schedule B:	8535.90.8020
ECCN:	EAR99
National Motor Freight:	061045, Boards Printed Circuit Elec



* See page 2 for technical characteristics

P/N MS27212-1-2 Specifications

Mounting Hole Diameter:	0.115 Inches
Dielectric Withstanding Voltage In Volts:	2500.0
Body Style:	Barrier Standoff
Center To Center Distance Between Terminals:	0.594 Inches
Board Construction:	Solid Construction
Center To Center Distance Between Mounting Facilities Parallel To Length:	0.594 Inches
Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:	0.344 Inches
Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:	0.218 Inches
Board Overall Length:	12.316 Inches
Board Overall Width:	0.688 Inches
Board Overall Height:	0.953 Inches
Board Height Excluding Terminals:	0.580 Inches
Base Thickness:	0.275 Inches
Mounting Facility Type And Quantity:	21 Unthreaded Hole
Nonfeedthru Terminal Type:	597 Single
Nonfeedthru Terminal Quantity:	20 Single
Terminal Pattern Arrangement:	Single Row
Terminal Design:	Nonfeedthru
Special Features:	20 Max Non-feed-through Terminals,cut To Desiredsize At Point Of Installation
Material:	Plastic Diallyl Phthalate Board
Material:	Steel Corrosion Resisting Terminals

How to Order

Order this terminal board from our inventory online by visiting <https://military-fasteners.com/electrical/terminal+boards/MS27212-1-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.