

Description

stud thread: 10-32, last number indicates number of studs, MS27212 series terminal

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2721222
Minimum Qty (MOQ):	5
NSN:	5940-00-220-3820
ECCN:	EAR99
National Motor Freight:	061260, Cable Terminals / Boxes / Housings Etc



P/N MS27212-2-2 Specifications

Mounting Hole Diameter:	0.115 Inches
Dielectric Withstanding Voltage In Volts:	2.5
Center To Center Distance Between Terminals:	0.750 Inches
Board Construction:	Solid Construction
Center To Center Distance Between Mounting Facilities Parallel To Length:	0.750 Inches
Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:	0.469 Inches
Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:	0.218 Inches
Board Overall Length:	1.936 Inches
Board Overall Width:	0.938 Inches
Board Overall Height:	1.079 Inches
Board Height Excluding Terminals:	0.789 Inches
Base Thickness:	0.328 Inches
Mounting Facility Type And Quantity:	3 Unthreaded Hole
Nonfeedthru Terminal Type:	597 Single
Nonfeedthru Terminal Quantity:	2 Single
Terminal Pattern Arrangement:	Single Row
Terminal Design:	Nonfeedthru
Material:	Plastic Diallyl Phthalate Board And Glass Fiber Board
Material Document And Classification:	Mil-p-19833,type Gdi-30f Mil Spec Single Material Response Board

How to Order

Order this terminal board from our inventory online by visiting <https://military-fasteners.com/electrical/terminal+boards/MS27212-2-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.