

Description

stud thread: 10-32, last number indicates number of studs, MS27212 series terminal

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2721225
Minimum Qty (MOQ):	1
NSN:	5940-00-546-4406
ECCN:	EAR99
National Motor Freight:	061045, Boards Printed Circuit Elec



* See page 2 for technical characteristics

P/N MS27212-2-5 Specifications

Mounting Hole Diameter:	0.115 Inches
Body Style:	Barrier Standoff
Terminal Row Quantity:	1
Center To Center Distance Between Terminals:	0.750 Inches
Board Construction:	Solid Construction
Center To Center Distance Between Mounting Facilities Parallel To Length:	0.750 Inches
Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:	0.469 Inches
Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:	0.218 Inches
Board Overall Length:	4.186 Inches
Board Overall Width:	0.938 Inches
Board Overall Height:	1.079 Inches
Board Height Excluding Terminals:	0.789 Inches
Base Thickness:	0.328 Inches
Mounting Facility Type And Quantity:	6 Unthreaded Hole
Nonfeedthru Terminal Type:	598 Single
Nonfeedthru Terminal Quantity:	10 Single
Terminal Pattern Arrangement:	Single Row
Terminal Design:	Nonfeedthru
Material:	Plastic Diallyl Phthalate Board And Glass Fiber Board
Material:	Steel Corrosion Resisting Terminals
Material Document And Classification:	Mil-p-19833 Mil Spec All Material Responses Board

How to Order

Order this terminal board from our inventory online by visiting <https://military-fasteners.com/electrical/terminal+boards/MS27212-2-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.